



Call [1.888.734.2947](tel:18887342947) or email info@allaxissystems.com
our friendly, helpful and experienced techs will help you get what you need.

Ronin 2

SPECIFICATIONS SHEET

Ronin 2 exists to let filmmakers capture the scene they see in their mind. Upgraded high torque motors allow it to support a wider range of cameras, resist high winds and G-forces caused when mounted to a car and keep it moving smoothly in flight.

FEATURES:

- Operation Modes
 - Underslung Mode
 - Upright Mode
 - Briefcase Mode
 - Handheld, Car Mount, Aerial & Tripod Mode
- Axis Modes
 - 3-axis
 - Pan-Lock
- Built-in, independent IMU module
- Advanced 32-Bit ARM Processor
- Specialized Gimbal Drive Motors with Encoders
- Dual Battery System
- Bluetooth Module
- D-Bus Receiver Supported
- 2.4 GHz/5.8 GHz Receiver
- Temperature Sensors
- Built-in Display
- Built-in GPS
- USB Type-C Connection
- Power and Video Signal through Slip Ring

SYSTEM SPECIFICATIONS:

- System Type: 3 axis gyro stabilized
- Weight: 14 lbs
- Min Height: 24"
- Width: 14"
- Max Payload: 30 lbs

